PROTECT

NATURAL LOOK SEALER

Sealer and repellent for a clear, natural look, UV stable finish

protecting porous mineral surfaces, including stone, unglazed tiles, concrete, brick, pavers, limestone, grout, terra cotta

PROTECT is a solvent based penetrating acrylic fluorinated copolymer that provides a durable, subsurface, transparent protective barrier against oil and water on porous mineral surfaces with excellent repellency and stain resistance.





KEEP OUT OF REACH OF CHILDREN NOT TO BE TAKEN READ ALL DIRECTIONS BEFORE OPENING











NATURAL LOOK SEALER

CHNICAL

Application:

Surface preparation should be cleaned, dust free and completely dry. PROTECT may be applied using a paint brush, roller, lambs wool applicator, or soft broom. Apply 2 – 3 soaking coats, leaving at least one hour between coats. Final cure one day.

Coverage: allow 5 – 8 square meters per litre. Resealing every 3 - 5 years.

Cleaning:

PROTECT can be removed from tools and equipment by applying Xylene.

Packaging:

PROTECT is supplied in 1, 4 and 20 litre containers. Shelf life is 12 months if packaging is kept tightly closed.

Precautions:

KEEP OUT OF REACH OF CHILDREN. READ SAFETY **DIRECTIONS BEFORE OPENING OR USING** FLAMMABLE LIQUID

BREATHING THE VAPOUR IS DANGEROUS. PROVIDE ADEQUATE VENTILATION DURING APPLICATION. DO NOT USE IN THE PRESENCE OF A NAKED FLAME. DO NOT SMOKE.

PROTECT is a highly combustible liquid. Store away from naked flames, sparks and heating. Avoid contact with skin and eyes. Wear protective goggles. If skin contact occurs, wash skin thoroughly. If swallowed do not induce vomiting, give a glass of water. If poisoning occurs seek medical advice

Refer to product Material Safety Data Sheet for additional safety information



