

PRODUCT OF THE MONTH

Sikafloor® Levelling Solutions

The installation thickness of Sikafloor® Levelling products ranges from Feather Edge to 120mm.



DOMESTIC



INDUSTRIAL



COMMERCIAL

The Sikafloor® Level Range includes

SikaTite Moisture Seal 1K - Unique Rapid Drying 1 component Moisture Barrier

Sikafloor 01 Primer - Versatile Porous & Non-porous Primer (Concentrate)

Sikafloor Level Pro Finish -Self-priming Skim Coat

Sikafloor Rapid Patch - Easy to apply Rapid Setting Mortar

Sikafloor Level PRO FS - Fast Setting Self Levelling Compound

Sikafloor Level PRO - Extended Setting Self Levelling Compound

Sikafloor Level Deep Fill -High Strength Screed / Deep Fill Compound

Sikafloor Level 30 -Industrial Internal & External Self Levelling Compound

SikaQuick 2500 - Concrete repair / replacement

Moisture Barrier & Primer



Description

Rapid drying acrylic moisture & vapour barrier + primer.

Uses

Interior green concrete barrier
Rapid drying primer
Barrier up to 93% RH

Characteristics

1st coat dry in 15 mins
2nd coat dry in 45 mins
Solvent-free & low VOC
Low consumption—high coverage

Area of use

Interior



Description

Versatile liquid primer designed to be diluted 1:3 with water for porous concrete surfaces or direct from packaging as a non-porous primer

Uses

Porous concrete substrates
Non-porous surfaces (tiles etc)

Characteristics

Solvent-free & low VOC
Low consumption / high coverage
Suitable for subfloor heating systems

Area of use

Interior

Skim Coat & Rapid Set



Description

Fast drying, patching & finishing compound that provides a smooth surface prior to installation of floor coverings

Uses

Skim coat under vinyl flooring

Characteristics

Self-priming
Low consumption / high coverage
Hard setting
Great workability—pot life

Area of use

Interior



Description

Ramping & repair mortar generally used prior to the installation of commercial & domestic flooring

Uses

Ramping / Patching concrete subfloors

Characteristics

Install flooring in as little as 60 minutes
High strength—45 Mpa
Good workability
Rapid setting
0 - 50mm

Area of use

Interior

BUILDING TRUST



**CONCRETE PROTECTION
PTY LTD**

155 Barkly Avenue, Burnley, Victoria. 3121

Tel: 03 9429 3377 Fax: 03 9427 0745

Email: info@conpro.com.au

Web: www.conpro.com.au

Sikafloor® Levelling Solutions

Levelling Underlayments



Description
Fast-setting self-levelling underlayment used to level a substrate prior to the application of commercial & domestic flooring

Uses
Install Ceramic Tiles etc 4-5 hrs
Install Carpets & Vinyls 14-16 hrs

Characteristics
High flow
Fast set
0-25mm

Area of use
Interior




Description
Extended set, self-levelling underlayment used to level a substrate prior to the application of commercial & domestic flooring

Uses
Install Ceramic Tiles etc 18 hrs
Install Carpets & Vinyls 24 hrs

Characteristics
Very high flow
Long pot life,
Great workability
0-50mm

Area of use
Interior

Deep Fill & Industrial Levelling



Description
Deep Fill underlayment for interior applications

Uses
Fill floor chasing
Creating falls to waist
Levelling uneven floors

Characteristics
Fast setting
High strength –30Mpa
Adjustable water demand
10-120mm

Area of use
Interior



Description
High performance self-levelling compound

Uses
Interior & Exterior leveller
Industrial Warehouse Floors

Characteristics
Fully trafficable surface
High flow
Suitable for subfloor heating systems
High Strength –40Mpa
3-30mm

Area of use
Interior & Exterior

Concrete Repair / Replacement



Description
Very Rapid Hardening Repair Mortar

Uses
Concrete replacement

Characteristics
Fast setting
Very high strength –100Mpa
5-150mm

Area of use
Interior & Exterior

For all technical information please refer to the 'Product Data Sheets' (PDS) prior to installation.

