

Supersedes: Aug 2010

Date of Issue:

June 2015

Not Hazardous According to Criteria of Worksafe Australia

Concrete Protection Pty Ltd

155 Barkly Avenue Burnley 94293377 Fax 94270745

MATERIAL SAFETY DATA SHEET

IDENTIFICATION

PRODUCT NAME:

ACRYLIC PAINT

OTHER NAMES:	Classic Paints Flat	UN No:	None allocated
	Classic Paints Low Sheen	DANGEROUS GOODS CLASS:	None allocated
	Classic Paints Acrylic Gloss	SUBSIDIARY RISK:	None allocated
	Classique Paint	HAZCHEM CODE:	None allocated
		POISON SCHEDULE:	Not scheduled

USE: General purpose water based acrylic paints for exterior and interior

PHYSICAL PROPERTIES

APPEARANCE:	Aqueous Coloured liquid. Viscous with a faint ammoniacal odour.	FLAMMABILITY LIMITS %:	Not applicable
			Not applicable
BOILING POINT:	100°	FLASHPOINT:	Not applicable
VAPOUR PRESSURE:	(20°C):23mbar(water)	SOLUBILITY IN WATER:	Miscible
SPECIFIC GRAVITY:	1.3	VAPOUR DENSITY (Air = 1)	Not relevant
OTHER PROPERTIES:	None relevant		

INGREDIENTS

CHEMICAL ENTITY	CAS No.	PROPORTION % (w/w)
A Co-polymer binder	None allocated	10 – 30%
B Inert Pigments	Various	30 – 60%
C Water	Not available	> 30%
D Other ingredients determined not to be hazardous	Not applicable	< 5%

Product Name: ACRYLIC PAINT

HEALTH HAZARD INFORMATION	
HEALTH EFFECTS - ACUTE	
No adverse health effects are expected if the product is used strictly as recommended in the instructions. If the product is mishandled, the following symptoms may arise:	
SWALLOWED:	Ingestion may result in gastric disturbances
EYE:	Prolonged and or repeated contact may result in irritation
SKIN:	Prolonged and or repeated contact may result in slight irritation
INHALED:	Inhalation may cause irritation to the respiratory tract. Breathing difficulties, coughing, CNS effects, pneumonitis and pulmonaty cedema.
HEALTH EFFECTS - CHRONIC	
There are no chronic effects associated with this material.	
FIRST AID	
SWALLOWED:	Immediately rinse mouth and then drink plenty of water. Do NOT induce vomiting. Seek medical attention.
EYE:	Hold eyelids open. Irrigate eyes with plenty of water. If irritation persists, seek medical advice.
SKIN:	Wash with soap and water.
INHALED:	Move victim to fresh air. Seek medical advice if effects persist.
FIRST AID FACILITIES:	Eye wash station and safety shower.
ADVICE TO DOCTOR	
Treat symptomatically.	

PRECAUTIONS FOR USE																					
EXPOSURE STANDARDS:	The product contains residual traces of various monomers in the ppm range. Observe exposure limits. If used in areas such as with an open window it is unlikely exposure limits will be exceeded. <table border="0"> <tr> <td>TWA:</td> <td>Acrylamide</td> <td>0.03 mg/m³</td> <td>(Category 2 Carcinogen, skin absorption).</td> </tr> <tr> <td></td> <td>Butyl acrylate</td> <td>10 ppm</td> <td></td> </tr> <tr> <td></td> <td>Styrene</td> <td>50 ppm</td> <td></td> </tr> <tr> <td></td> <td>Ethyl benzene</td> <td>100 ppm</td> <td></td> </tr> <tr> <td></td> <td>Formaldehyde</td> <td>1 ppm</td> <td></td> </tr> </table>	TWA:	Acrylamide	0.03 mg/m ³	(Category 2 Carcinogen, skin absorption).		Butyl acrylate	10 ppm			Styrene	50 ppm			Ethyl benzene	100 ppm			Formaldehyde	1 ppm	
TWA:	Acrylamide	0.03 mg/m ³	(Category 2 Carcinogen, skin absorption).																		
	Butyl acrylate	10 ppm																			
	Styrene	50 ppm																			
	Ethyl benzene	100 ppm																			
	Formaldehyde	1 ppm																			
ENGINEERING CONTROLS:	Open air or good general ventilation, which will ensure those exposure standards, are not exceeded.																				
PERSONAL PROTECTION																					
EYES:	Use safety glasses.																				
HANDS/ARMS:	Any impervious gloves, long sleeves, barrier cream.																				
RESPIRATORY:	None required under normal conditions of use.																				
CLOTHING:	Boots, long sleeved overalls.																				
FLAMMABILITY																					
Product is non-flammable and non combustible.																					

Product Name: ACRYLIC PAINT

SAFE HANDLING INFORMATION**STORAGE AND TRANSPORT**

DANGEROUS GOODS CLASS:	Not classified	SUBSIDIARY RISK:	Not classified
STORAGE:	Store in a cool place, out of direct sunlight. Do not store above 40°C or below 5°C.		
TRANSPORT:	This product is not a Dangerous Substance for the purposes of transport. No special transport requirements are necessary.		
INCOMPATIBILITIES:	None known.		

SPILLS AND DISPOSAL

Wear rubber gloves/goggles to avoid splashes. Prevent run-off into drains and waterways. Cover with absorbent material, rags or sand for example, for spills and leaks. Scrape up and place into suitable, labeled containers for disposal. Dispose of as per relevant Local State or Federal Regulations. Empty containers may contain product residue. Follow safety procedures until container has been cleaned. Avoid breathing vapours.

Dispose strictly in accordance with local industrial waste or environmental protection regulations.

FIRE / EXPLOSION HAZARD

HAZCHEM CODE:	Not applicable
EXTINGUISHING MEDIA:	Not applicable
FIRE-FIGHTING RECOMMENDATIONS:	Not applicable

OTHER INFORMATION**CONTACT POINT**

Technical Services

Telephone: (BH) 03 94293377

(AH) 1800 807 001

The information in this document is given to provide details of known hazards and is prepared from sources believed reliable, and can only be used for safety and health purposes. The Company makes no warranty that it is in all cases correct and sufficient. Prepared along Worksafe Guidelines. This Material Safety Data Sheet can only be copied in its entirety without any alterations.