

Contec

GROUT



Quick Set Cement base Grout

TECHNICAL DATA

Contec GROUT provides a quick setting cement compound with waterproofing capabilities.

- general purpose grouting
- fill core holes, rod holes and concrete defects
- grout between precast panels and other joints
- concrete waterproofing
- concrete repair

Contec GROUT contains no metals, calcium chloride or other corrosive ingredients. **Contec GROUT** contains chemicals which react with concrete, forming a waterproofing crystalline structure within the pores of the concrete.

APPLICATION DIRECTIONS

Remove all unsound concrete from the area to be treated. Clean concrete surfaces of all contaminants and loose pieces. Substrate must have a coarse open pore surface for adequate penetration and adhesion.

Pre-wet the surface and remove excess water prior to application. Add dry powder to pre-measured clean water and mix using a paddle mortar mixer or similar method until the mixture is of suitable consistency.

Apply by trowel within 5 minutes of mixing.

MIXING DIRECTIONS

Thoroughly mix approximately 2 parts of **Contec GROUT** with 1 part clean water using small quantities at a time as the product is unusable after setting takes place. Adjust water for your required consistency.

SAFETY PRECAUTIONS

Avoid contact with eyes. Avoid contact with skin. Wear rubber gloves.

FIRST AID

If poisoning occurs contact a doctor or Poisons Information Centre. If swallowed do NOT induce vomiting, give a glass of water. If skin contact occurs remove contaminated clothing and wash skin thoroughly. If in eyes, hold eyes open, flood with water for at least 15 minutes and contact a doctor.

PACKAGING

6.25 kg pail
12.5 kg pail

