

# Contec

# PLUG



Rapid Set Concrete Repair Compound

TECHNICAL DATA

**Contec Plug** when mixed with water to a putty consistency can be used to stop the seepage or flow of water through cracks or holes in concrete. **Contec Plug** sets in a short period of time to a completely waterproof seal and continues to harden until its strength exceeds that of the concrete being repaired.

**Contec Plug** contains no metals, calcium chloride or other corrosive ingredients.

#### APPLICATION DIRECTIONS

Remove all unsound concrete from the area to be treated. Form a chase in the concrete in the area of the leak or along the line of a crack. Chase a minimum depth of 30mm. The width no greater than the depth. Apply mixed **Contec Plug** by hand to the prepared chase and hold firmly in position until the mortar is sufficiently hardened to remain in place. In the case of a crack, progress with the application in sections leaving the most serious area until the last. For repairs against high water pressures a plastic bleed hose may be used to allow the repair to harden. When hard remove the hose and repair the small hole.

#### MIXING DIRECTIONS

Thoroughly mix approximately 2 parts of **Contec Plug** with 1 part clean water using small quantities at a time as the product is unusable after setting takes place. Adjust water to give a putty like consistency.

#### SAFETY PRECAUTIONS

Avoid contact with eyes. Avoid contact with skin. Wear rubber gloves.

#### FIRST AID

If poisoning occurs contact a doctor or Poisons Information Centre. If swallowed do NOT induce vomiting, give a glass of water. If skin contact occurs remove contaminated clothing and wash skin thoroughly. If in eyes, hold eyes open, flood with water for at least 15 minutes and contact a doctor.

#### PACKAGING

2.5 kg can  
6.25 kg pail  
12.5 kg pail

