

DECRA COAT

a
decorative
and
durable
floor
coating
available
in a
variety of
colours

Easy to use, long wearing, interior or exterior coating for concrete, masonry and timber surfaces. Water based quality acrylic floor coating. Available in a wide variety of colours (deep base).

DECRA COAT provides resistance to many chemicals, oils, fats, acids and alkalis. It is an ideal coating where waterproofing, dust proofing and an attractive appearance is required. Suitable for internal and/or external application. Excellent UV light resistance and weathering ability.

TYPICAL APPLICATIONS:

Concrete - Masonry – Timber:

factory floors, balconies, concrete floors and driveways. DECRA COAT is also ideal for line marking car parks.



**AUSTRALIAN MADE
AND OWNED**

technical information available on web page
Meeting Australian Standards

DECRA COAT

TECHNICAL DATA

PREPARATION

Remove any prior coatings by grit blasting or solvent strippers. Acid etch concrete and masonry surfaces with a 10% solution of Hydrochloric acid, and allow 4 hours to dry. Surfaces should be clean, dry and free of grease, oil and other contaminants. Patch to produce a smooth surface.

APPLICATION

DECRA COAT may be applied using spray, brush or roller. Ideally, 2 or more coats should be applied at intervals of not less than 6 hours. Do not apply when rain is imminent or when the air or surface temperature is below 12° C or above 32° C. First coat should be diluted with 10% water.

COVERAGE

Approximately 8-12 square metres per coat. Minimum 2 coats per application.

CURING

Depending on ambient conditions DECRA COAT will accept light foot traffic in 6 to 12 hours full cure in 2-3 days.

CLEAN UP

Brushes and equipment clean up in water.

PRECAUTIONS

Concrete paving may not have a moisture barrier installed and if porous the capillary action of moisture may create adhesion failure. DECRA COAT will seal pores of the substrate and therefore may reduce traction..

COLOURS

Most colours are available, apart from very dark shades. DECRA COAT is a deep base product which can be colour matched to most formulas.

Recommendations, suggestions or statements made in this bulletin are intended for the assistance of our customers. They are based upon our experience and judgement but must not be regarded as amounting to a legal warranty or as involving any liability on our part and must be read in conjunction with and subject to the conditions of sale which apply to all goods supplied by this company.



Refer to product Material Safety Data Sheet for additional safety information