MICROL PRIMER

A single pack primer suitable for applied waterproofing systems.

USES

As a Sealer or primer for interior and/or exterior surfaces including timber, concrete, fibrous cement, brick, concrete block, concrete tilt panels, masonry, off form concrete, Hebel, Block, previously painted or metal surfaces.

BENEFITS

- # Single Pack;
- * No mixing, use straight from pail;
- ★ Ease of Application brush, roller or broom;
- * Protection against carbonation of concrete surfaces.

GRADES

Microl Primer is available in -

ACRYLIC: Available for use on all substrates, previously painted surfaces, residual bitumen membranes and coatings. New concrete, precast tilt panels, and Hebel Block.

PROPERTIES ACRYLIC

Colour Grey

Solids

Water Resistance Excellent

Flammability Non-Flammable

SURFACE PREPARATION

All surfaces to be primed shall be free of dirt, oil, wax and loose matter. All defects shall be made good prior to application.

APPLICATION

Microl Primer should be mixed thoroughly and may be applied directly from the pail by brush, roller, or broom.

COVERAGE

Application rate will vary according to porosity of surface being treated. Average application rate is $6 - 8m^2$ per litre.

DRYING TIME

Microl Acrylic Primer: Approx. 30 minutes @ 20°C and 40% R.H.

CLEAN UP

Microl Acrylic Primer: Use water before coating cures.

PACKAGING 1 Litre 5 Litre 15 Litre 20 Litre

Microl Acrylic Primer: ✓ ✓ ✓ ✓ ✓

STORAGE

Unopened material should be stored in a cool dry place away from heat.

AUSTRALIAN MADE AND OWNED