

# PROTECT

## NATURAL LOOK SEALER

Rev. 2018

FLOORING

### Sealer and repellent for a clear, natural look, UV stable finish

#### Product Description

PROTECT sealer is ideal for protecting porous mineral surfaces, including stone, unglazed tiles, concrete, brick, pavers, limestone, grout, terra cotta

PROTECT is a solvent based penetrating acrylic fluorinated copolymer that provides a durable, subsurface, transparent protective barrier against oil and water on porous mineral surfaces with excellent repellency and stain resistance.



#### Product Features

- Penetrative sealer on most surfaces
- Highly effective surface repellent
- Highly trafficable, suitable for trucks, forklifts and other vehicles
- Extremely durable, but is subject to failure in chlorine environments
- Economical
- Easy to apply, but note health & safety requirements
- Easy to maintain the surface
- Available in clear, natural look

#### Hazard Warnings

**POISON**

**KEEP OUT OF REACH OF CHILDREN  
NOT TO BE TAKEN  
READ ALL DIRECTIONS BEFORE OPENING**



# PROTECT

## NATURAL LOOK SEALER

### TECHNICAL DATA

**Application:** Surface preparation should be cleaned, dust free and completely dry. PROTECT may be applied using a paint brush, roller, lambs wool applicator, or soft broom. Apply 2 – 3 soaking coats, leaving at least one hour between coats. Final cure one day.

**Coverage:** Allow 5 – 8 square meters per litre. Resealing every 3 – 5 years.

**Cleaning:** PROTECT can be removed from tools and equipment by applying Xylene.

**Packaging:** PROTECT is supplied in 1, 4, 10 and 20 litre containers. Shelf life is 12 months if packaging is kept tightly closed.

**Precautions:** **KEEP OUT OF REACH OF CHILDREN. READ SAFETY DIRECTIONS BEFORE OPENING OR USING FLAMMABLE LIQUID**  
**BREATHING THE VAPOUR IS DANGEROUS. PROVIDE ADEQUATE VENTILATION DURING APPLICATION. DO NOT USE IN THE PRESENCE OF A NAKED FLAME. DO NOT SMOKE.**

**Prevention:** Wear protective gloves. Wear eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating, lighting and all material-handling equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Keep container tightly closed. Use only outdoors or in well-ventilated area. Avoid release to the environment. Avoid breathing vapour. Wash hands thoroughly after handling.

*Refer to product Safety Data Sheet for additional safety information*

