

PRODUCT OF THE MONTH

NEW!

Sikafloor® Level Top

Cement based self-levelling & smoothing compound

Uses

- ◆ Recommended underlayment for all commercial & domestic vinyls, carpets, timber/laminates, tiles/stone.
- ◆ Levelling of uneven concrete substrates during or after construction.
- ◆ **Interior applications.**
- ◆ Install from 2-30mm in one application.

Advantages

- ◆ Very low VOC.
- ◆ Non-combustible.
- ◆ Simple mix & apply—No slaking or re-mixing required.
- ◆ Able to be applied across large floor areas in a single application
- ◆ Good pot life and working time.
- ◆ Pump or manual application.



Size—20kg Bag

Appearance—Grey

Also available



aus.sika.com

BUILDING TRUST



**CONCRETE PROTECTION
PTY LTD**

155 Barkly Avenue, Burnley, Victoria. 3121

Tel: 03 9429 3377 Fax: 03 9427 0745

Email: info@conpro.com.au

Web: www.conpro.com.au

PRODUCT OF THE MONTH

Sikafloor® Level Top

Step 1 Surface Preparation

- ◆ Concrete must accept water penetration. Be structurally sound, clean, dry & free of surface contaminants.

Step 2 Priming

- ◆ Correct amount of primer should always be applied to give good penetration and film build.



Step 3 Mixing

- ◆ Mix product with high speed drill & mixing paddle for 2 minutes.



Step 4 Application

- ◆ Pour the mixed product onto the prepared substrate and work to heights required.



Step 5 Drying

- ◆ Levelling compound is ready to take floor coverings after 18 + hours @ 23°C



For all technical information please refer to the 'Product Data Sheet' (PDS)



aus.sika.com

BUILDING TRUST



**CONCRETE PROTECTION
PTY LTD**

155 Barkly Avenue, Burnley, Victoria. 3121

Tel: 03 9429 3377 Fax: 03 9427 0745

Email: info@conpro.com.au

Web: www.conpro.com.au