



MICROL 2100 SOLVENT PRIMER

BITUMEN Primer

ADCHEM NO. 19374

Microl 2100 Solvent Primer is used as a general purpose primer, but specifically used as a Bitumen Primer

Application

Surface conditions can vary, particularly with an old bitumen coating. The applicator has to assess the condition of the surface. More difficult surfaces may require a more liberal coverage to re-activate the surface. Application can be done with roller or brush. Always mix well prior to use

Coverage

Approximately 8 m² per litre

Cleaning

MICROL SOLVENT PRIMER can be removed from tools and equipment by applying Xylene.

Packaging

MICROL SOLVENT PRIMER is supplied in 1, 4, 10 and 20 litre drums. Shelf life is 12 months if drum kept tightly closed.

Handling Precautions

MICROL SOLVENT PRIMER is a combustible liquid. (Category 3)

Provide adequate ventilation.

Store away from naked flames, sparks and heating.

Avoid contact with skin and eyes. Skin corrosion or irritation (Category 2)

Wear protective equipment and clothing. If skin contact occurs, wash skin thoroughly. If swallowed do not induce vomiting, give a glass of water. If poisoning occurs seek medical advice

Refer to product Safety Data Sheet for additional safety information

POISON

**KEEP OUT OF REACH OF CHILDREN
NOT TO BE TAKEN
READ ALL DIRECTIONS BEFORE OPENING**



**CONCRETE PROTECTION
PTY LTD**

155 Barkly Avenue, Burnley, Victoria. 3121

Tel: 03 9429 3377 Fax: 03 9427 0745

Email: info@conpro.com.au Web: www.conpro.com.au

WATERPROOFING