

UNISEAL

NATURAL LOOK – REPELLENT SEALER

Solvent based, penetrating, UV sealer for mineral surfaces

CONCRETE
PAVERS
BRICK
LIMESTONE
TERRA COTTA

Product Description

This sealer is ideal for protecting porous mineral surfaces, including stone, unglazed tiles, concrete, brick, pavers, limestone, terra cotta

The product is a solvent based penetrating sealer with silane and siloxane that provides a durable, subsurface, transparent protective barrier with excellent water repellency and stain resistance.

Product Features

- Penetrative sealer on most surfaces
- Highly effective surface repellent
- Highly trafficable, suitable for trucks, forklifts and other vehicles
- Extremely durable, but is subject to failure in chlorine environments
- Economical
- Easy to apply, but note health & safety requirements

Hazard Warnings

POISON

**KEEP OUT OF REACH OF CHILDREN
NOT TO BE TAKEN
READ ALL DIRECTIONS BEFORE OPENING**



December 2024

UNISEAL

NATURAL LOOK – REPELLENT SEALER

Application: Solvent based, penetrating, UV sealer for mineral surfaces

Application: Surface should be clean, dust free and completely dry. The product may be applied using a paint brush, roller, lambs wool applicator, or soft broom. Apply 2 – 3 soaking coats, leaving at least one hour between coats. Final cure one day.

Coverage: Allow 5 – 8 square meters per litre, per coat.
Resealing every 3 – 5 years.

Cleaning: Use Xylene or strong thinner to clean tools & equipment..

Packaging: Supplied in 1, 4, 10 and 20 litre containers.
Shelf life 12 months if packaging is kept tightly closed.

Precautions: **KEEP OUT OF REACH OF CHILDREN. READ SAFETY DIRECTIONS BEFORE OPENING OR USING FLAMMABLE LIQUID**
BREATHING THE VAPOUR IS DANGEROUS. PROVIDE ADEQUATE VENTILATION DURING APPLICATION. DO NOT USE IN THE PRESENCE OF A NAKED FLAME. DO NOT SMOKE.

Prevention: Wear protective gloves. Wear eye or face protection.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating, lighting and all material-handling equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Keep container tightly closed. Use only outdoors or in well-ventilated area. Avoid release to the environment. Avoid breathing vapour. Wash hands thoroughly after handling.
Refer to product Safety Data Sheet for additional safety information

